



CELLO PRODUCTS

YOUR COPPER FITTING CONNECTION & MORE

Carbon Steel Press

- Available ½ - 2"
- Over 275 SKU's available
- Compatible with most pressing tools
- Stainless Steel grip rings for optimal pull out resistance
- 100% factory tested
- Shrink wrapped ends fall off to provide visual confirmation the fitting has been pressed
- Improperly pressed fittings will leak under low pressure
- Zinc Nickel coating for corrosion-resistant performance
- 15 year Limited Warranty



Carbon Steel fittings are for non-potable plumbing, natural gas, and LPG systems, designed to be used with schedule 10 to 40 Carbon Steel Pipe. Colour coded dots on the fitting indicate whether it's for non-potable water or gas.

- Yellow indicates an HBNR O-ring for gas
- Green indicates an EPDM O-ring for water



Compliant with NFPA 13



FM Approvals Class:
1920, Pipe Couplings and
Fittings for Aboveground
Fire Protection Systems



**ANSI/CAN/UL 213, Rubber Gasketed
Fittings for Fire-Protection Service**
**ANSI/CAN/UL/ULC 199, Automatic
Sprinklers for Fire Protection Service**



**IAPMO/ANSI/CAN Z1117,
Press Connections**



The Cello Carbon Steel Press System does not require gas shielded welding, brazing, or threading. There is no fire hazard and no fire duty certificate is required.

ALSO AVAILABLE

- Wrot & Cast Solder Fittings
- Carbon Steel Press Fittings
- No Lead Threaded Brass Fittings
- Plastic Pex & F1960 Fittings
- Dielectric Unions
- No Lead Cast Swing Checks
- Copper Press Fittings
- Ball Valves - IPS CxC Pex & Press
- No Lead Threaded Brass Nipples
- No Lead Pex & F1960 Fittings
- No Lead Push Fittings
- Supply Stops

